



Jaguar 200

Electrical submersible drainage pump

50 Hz



Model	H
Discharge Connection	6"
Rated motor power motor (kW/HP)	150/200
Maximum power consumption (KW)	155
Rotational speed (R.P.M.)	2950
Rated current at 380V	272A
Solids passage	10 mm
Dimensions H/W.	1820/1070 mm
Weight (kg)	1740

Classification

Electrical submersible drainage pump

Electric motor

Three-phase squirrel cage motor, insulation class: F

Protection

Pump: IP 68

Motor: Thermocontact in the stator winding
PT100 temperature sensor in the fixed bearing

Cable entry: Double protection with EPDM seal and epoxy resin that prevents water from entering the motor

Starting type

Soft starter

Cable - SubCab

4Gx50mm²+2x1.5mm², length 20 meters* (02)

Discharge connection

*Flange type ASME B16.5: Ø6" (Class 300)

Mechanical seals

Upper Seal Material: Silicon Carbide - Silicon Carbide
Lower Seal Material: Silicon Carbide - Silicon Carbide

Bearings

Upper: Two single row angular contact ball bearing
Lower: Cylindrical single-row roller bearing with C3 clearance

Materials

Casted parts: Nodular cast iron
Strainer: Stainless steel AISI 304
Motor shaft: Stainless steel AISI 431
Impellers: High chrome iron casting
Diffusers: High chrome iron casting
Suction cover: High chrome iron casting
Screws and nuts: Stainless steel AISI 304

Limitations

Maximum submersion depth: 20m (66ft)
Maximum liquid temperature: 40°C (104°F)
Maximum liquid density: 1100 kg/m³ (68lbs/ft³)
Allowed pH range: 5 to 11

This pump must be connected to an external electrical panel with adequate protection

(*) The specifications can be modified if required by the client